

Ultraviolet Germicidal Disinfection Lamp

GT-GL1901UVC



Kill the virus

36W

Stronger
Sterilization
Power

**Human
sensor**

Sensitive



3 Time options
15/30/60

Flexible setting of UV
light radiation time,
15/30/60 minutes
adjustable.

Control panel



**3pcs
Intelligent
Human sensor**

Ensure safety

3pcs infrared human sensors are evenly panoramic distributed to prevent people or pets from being exposed to ultraviolet radiation.



Applicable place



Home



Hospital



Office



Hotel

0887868723

ESPECIFICACIONES TECNICAS	
Potencia	36 wattios
Alarma Sonora	70 dB
Voltaje de Alimentación	110 – 220 VAC
Corriente de Consumo	0,18 A
Distancia de activación del Sensor para desconexión por presencia humana	3 metros
Temporizador Automático Configurable	15 / 30 / 60 Minutos
Tiempo de Irradiación UV	Display Digital
Temperatura de Trabajo	-10 ° C a +50 ° C
Humedad de Trabajo	10 a 95% HR
Estándares	IEC60335-1, IEC60335-2-65, EN61347-1, EN61347-2-3
Nivel de Protección	IP20
Dimensiones	Diámetro 120 mm x 460 mm